

SPECIFICATIONS

# AGRIXTRA 65 SERIES

## FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
650/65R42	158D / 161A8	TL	DW20B	DW20A	56

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
645	1912	863	5717	925	47	619

Max load per tyre (kg) / Inflation pressure (bar)									
	(km/h)	0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	<b>10 LT</b>	3430	3885	4345	4800	5260	5715		6375
	<b>30 LT / 10 HT</b>	2935	3325	3715	4105	4495	4890		
	<b>40</b>		3165	3535	3910	4280	4625		
	<b>50</b>		3035	3390	3750	4105	4465		
	<b>65</b>			3230	3570	3910	4250		