

SPECIFICATIONS

# AGRIXTRA

## 85 SERIES

### FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
280/85R24	11.2R24	115A8 / 115B	TL	W10	W9	40

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
292	1086	491	3247	525	36	78

Max load per tyre (kg) / Inflation pressure (bar)									
		0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	1100	1205	1315	1425	1535	1645		1825
	30 LT / 10 HT		955	1040	1125	1215	1300		
	40 & 50		890	970	1055	1135	1215		