

SPECIFICATIONS

AGRIXTRA

85 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



| Size | 2nd Size marking | LI/SS | Type | Recommended Rim (Inch) | Authorised Rim (Inch) | Tread Depth (mm) |
|-----------|------------------|--------------|------|------------------------|-----------------------|------------------|
| 460/85R34 | 18.4R34 | 147A8 / 147B | TL | W16L | W15L DW15L DW16L | 51 |

| Section Width on Rec Rim (mm) | Overall Diameter (mm) | Static Loaded Radius (mm) | Rolling Circumference (mm) | Speed Radius Index | Rolling Circumference Index | 75% of Internal volume (l) |
|-------------------------------|-----------------------|---------------------------|----------------------------|--------------------|-----------------------------|----------------------------|
| 475 | 1646 | 737 | 4922 | 775 | 44 | 348 |

| Max load per tyre (kg) / Inflation pressure (bar) | | | | | | | | | |
|---|---------------|------|------|------|------|------|------|-----|------|
| | (km/h) | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 | 1.8 | 1.9 |
| Service Speed (km/h) | 10 LT | 2780 | 3055 | 3335 | 3610 | 3890 | 4165 | | 4615 |
| | 30 LT / 10 HT | | 2415 | 2630 | 2850 | 3070 | 3290 | | |
| | 40 & 50 | | 2255 | 2460 | 2665 | 2870 | 3075 | | |