

SPECIFICATIONS

AGRIXTRA

85 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
520/85R38	20.8R38	155A8 / 155B	TL	DW18L	W16L DW16L W18L	53

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
536	1849	827	5529	875	46	511

Max load per tyre (kg) / Inflation pressure (bar)									
		0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	3500	3850	4200	4550	4900	5250		5815
	30 LT / 10 HT		3040	3315	3595	3870	4145		
	40 & 50		2840	3100	3360	3615	3875		