

SPECIFICATIONS

AGRIXTRA 85 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
520/85R42	20.8R42	157A8 / 157B	TL	DW18L	W16L DW16L W18L	53

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
536	1951	878	5833	925	47	552

Max load per tyre (kg) / Inflation pressure (bar)									
	(km/h)	0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	3725	4100	4470	4845	5215	5590		6190
	30 LT / 10 HT		3235	3530	3825	4120	4415		
	40 & 50		3025	3300	3575	3850	4125		