

MAXAM AGRIXTRA 70

Wide profile 70-series tire for extra flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal	# of lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951100	360/70R24	122A8/B	TL	W11	W10, W12	13.9	352	45.4	1152	20.3	516	135.6	3444	37 550	50 40	139 63	31.2 118	17 x 2	158 1021
951101	380/70R24	125A8/B	TL	W12	W11, W13	14.8	376	46.9	1190	20.9	531	140.1	3558	37 575	52 41	156 71	37.0 140	17 x 2	174 1123
951103	420/70R24	130A8/B	TL	W13	W12, W14L	16.7	424	49.1	1248	21.8	554	147.0	3732	38 600	53 42	182 82	47.3 179	18 x 2	201 1294
V951129	480/70R24	138D/141A8	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	18.9	479	51.8	1316	22.8	580	154.9	3935	39 625	55 44	228 103	63.1 239	18 x 2	249 1607
951209	360/70R28	125A8/B	TL	W11	W10, W12	14.3	364	49.3	1251	22.3	566	147.3	3740	32 600	50 40	148 67	34.8 132	18 x 2	174 1123
951102	380/70R28	127A8/B	TL	W12	W11, W13	15.0	380	50.9	1293	23.0	583	152.2	3866	39 575	52 41	170 77	41.7 158	18 x 2	185 1191
951105	420/70R28	133A8/B	TL	W13	W12, W14L	16.6	422	53.1	1349	23.8	604	158.8	4034	40 650	53 42	198 90	52.8 200	18 x 2	217 1403
951104	480/70R28	140A8/B	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	19.1	484	56.0	1421	24.9	632	167.3	4249	41 675	55 44	249 113	71.0 269	19 x 2	264 1702
V951130	480/70R30	152D/155A8	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	19.0	483	58.2	1478	26.0	660	174.0	4419	42 700	60 48	265 120	74.4 282	19 x 2	241 1554

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Continued

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal	# of lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951112	520/70R30	145A8/B	TL	W16L	W15L, W18L	20.3	515	60.5	1536	26.9	683	180.9	4593	42 725	63 50	304 138	90.0 341	20 x 2	306 1974
V951131	480/70R34	155A8/B	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	18.9	479	62.2	1580	28.0	711	186.0	4724	43 750	60 48	288 130	82.1 311	19 x 2	263 1696
951121	520/70R34	148A8/B	TL	W16L	W15L, W18L	20.1	511	64.6	1640	28.9	735	193.1	4904	44 775	63 50	332 150	99.3 376	20 x 2	332 2145
951214	480/70R38	145A8/B	TL	W15L	W14L, W16L	19.4	493	66.2	1681	30.0	762	197.9	5026	44 800	57 45	319 145	89.5 339	20 x 2	306 1974
951108	520/70R38	150A8/B	TL	W16L	W15L, DW15L, DW16L, W18L, DW18L	20.3	516	68.9	1749	31.0	788	205.9	5230	45 825	63 50	366 166	109.6 415	20 x 2	354 2281
951109	580/70R38	155A8/B	TL	W18L	DW18L	22.8	578	71.9	1827	32.2	819	215.1	5463	46 875	71 56	444 202	138.9 526	21 x 2	409 2638
951124	620/70R42	166D/169A8	TL	DW20B		24.6	625	76.2	1935	34.3	872	227.8	5786	47 925	73 58	512 232	163.7 620	22 x 2	419 2706

MAXAM **AGRIXTRA 70**

AGRIXTRA 70 LOAD AND INFLATION

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)												
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi	
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar	
360/70R24	122A8/B	5/10 LT	2985/1355	3285/1490	3585/1625	3880/1760	4180/1895	4485/2035							4960/2250
		25/40 & 30/50	2425/1100		2645/1200	2865/1300	3085/1400	3305/1500							
380/70R24	125A8/B	5/10 LT	3285/1490	3615/1640	3945/1790	4275/1940	4595/2085	4925/2235							5455/2475
		25/40 & 30/50	2670/1210		2910/1320	3155/1430	3395/1540	3640/1650							
420/70R24	130A8/B	5/10 LT	3780/1715	4165/1890	4540/2060	4915/2230	5300/2405	5675/2575							6285/2850
		25/40 & 30/50	3075/1395		3350/1520	3625/1645	3915/1775	4190/1900							
480/70R24	138D/141A8	5/10 LT	4200/1905	4765/2160	5315/2410	5875/2665	6440/2920	7000/3175							7805/3540
		40/65	3960/1795		4365/1980	4785/2170	5205/2360								
360/70R28	125A8/B	5/10 LT	3285/1490	3615/1640	3945/1790	4275/1940	4595/2085	4925/2235							5455/2475
		25/40 & 30/50	2670/1210		2910/1320	3155/1430	3395/1540	3640/1650							
380/70R28	127A8/B	5/10 LT	3485/1580	3835/1740	4180/1895	4530/2055	4885/2215	5225/2370							5785/2625
		25/40 & 30/50	2835/1285		3085/1400	3340/1515	3605/1635	3860/1750							
420/70R28	133A8/B	5/10 LT	4100/1860	4510/2045	4925/2235	5335/2420	5745/2605	6150/2790							6810/3090
		25/40 & 30/50	3330/1510		3640/1650	3935/1785	4245/1925	4540/2060							
480/70R28	140A8/B	5/10 LT	4980/2260	5480/2485	5975/2710	6470/2935	6965/3160	7475/3390							8265/3750
		25/40 & 30/50	4045/1835		4410/2000	4775/2165	5150/2335	5510/2500							
520/70R30	145A8/B	5/10 LT	5775/2620	6350/2880	6935/3145	7505/3405	8090/3670	8665/3930							9590/4350
		25/40 & 30/50	4685/2125		5115/2320	5545/2515	5965/2705	6395/2900							
520/70R34	148A8/B	5/10 LT	6270/2845	6900/3130	7530/3415	8155/3700	8785/3985	9415/4270							10415/4725
		25/40 & 30/50	5095/2310		5555/2520	6020/2730	6480/2940	6945/3150							
480/70R38	145A8/B	5/10 LT	5775/2620	6350/2880	6935/3145	7505/3405	8090/3670	8665/3930							9590/4350
		25/40 & 30/50	4685/2125		5115/2320	5545/2515	5965/2705	6395/2900							
520/70R38	150A8/B	5/10 LT	6670/3025	7340/3330	8005/3630	8675/3935	9335/4235	10010/4540							11080/5025
		25/40 & 30/50	5410/2455		5910/2680	6405/2905	6890/3125	7385/3350							
580/70R38	155A8/B	5/10 LT	7715/3500	8490/3850	9260/4200	10030/4550	10805/4900	11575/5250							12820/5815
		25/40 & 30/50	6260/2840		6835/3100	7410/3360	7970/3615	8545/3875							
620/70R42	166D/169A8	5/10 LT	8005/3630	9075/4115	10145/4600	11210/5085	12280/5570	13350/6055	13935/6320	14530/6590		15125/6860	15720/7130	17530/7950	
		40/65	7540/3420		8335/3780	9130/4140	9925/4500	10365/4700	10805/4900		11245/5100	11685/5300			

*LT = Low Torque

AGRIXTRA 70 LOAD AND INFLATION

Continued

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)						
			12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi
			0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar
480/70R30	152D/155A8	5/10 LT	5195/2355	5800/2630	6415/2910	7025/3185	7640/3465	8005/3630	8380/3800
		40/65	4310/1955		4775/2165	5225/2370	5680/2575	5955/2700	6230/2825
480/70R34	155A8/B	5/10 LT	5975/2710	6515/2955	7055/3200	7595/3445	8135/3690	8535/3870	8930/4050
		25/40 & 30/50	4410/2000	4805/2180	5205/2360	5610/2545	6010/2725	6295/2855	6595/2990
Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg) <i>continued</i>						
			32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	
			2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	
480/70R30	152D/155A8	5/10 LT	8755/3970	9120/4135	9470/4295	9825/4455	10175/4615	10530/4775	
		40/65	6505/2950	6780/3075	7045/3195	7310/3315	7565/3430	7830/3550	
480/70R34	155A8/B	5/10 LT	9315/4225	9715/4405	10175/4615	10640/4825	11115/5040	11575/5250	
		25/40 & 30/50	6880/3120	7165/3250	7510/3405	7860/3565	8205/3720	8545/3875	

*LT = Low Torque

