

MAXAM AGRIXTRA H

Large volume R1W tires designed specifically for harvesting machines. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| Item Number | Size | Replaces | LI / SS | Type | Rim (Rec.) | Rim (Alter.) | S.W. | | O.D. | | S.L.R. | | R.C. | | R.C.I. S.R.I. | Tread Depth 32nds mm | Weight lbs kg | 75% of Int. Vol. gal l | # of Lugs | Gross Flat Plate sq in sq cm |
|-------------|------------|----------|------------|------|------------|--------------|-------------------------|------|------|------|--------|-----|-------|------|---------------|----------------------|---------------|------------------------|-----------|------------------------------|
| | | | | | | | in | mm | in | mm | in | mm | in | mm | | | | | | |
| V951137 | 1000/50R25 | | 172D/175A8 | TL | 36.0 TH | W14L | 41.7 | 1059 | 66.4 | 1685 | 28.6 | 727 | 198.4 | 5038 | 44 800 | 72 57 | 849 385 | 263.5 998 | 20 x 2 | 499 3217 |
| V951206 | 620/75R26 | 23.1R26 | 166A8/B | TL | DW20B | | 24.1 | 611 | 58.7 | 1491 | 24.8 | 629 | 175.5 | 4458 | 44 700 | 66 53 | 501 227 | 124.6 472 | 18 x 2 | 360 2320 |
| | 750/50R26 | | 157D/160A8 | | | | New Size in Development | | | | | | | | | | | | | |
| V951118 | 750/65R26 | 28LR26 | 166D/169A8 | TL | DW25B | DW23B | 30.1 | 764 | 64.4 | 1636 | 28 | 711 | 192.6 | 4892 | 44 775 | 71 56 | 529 240 | 172.4 653 | 20 x 2 | 419 2706 |
| V951126 | 650/75R32 | 24.5R32 | 172D/175A8 | TL | DW21B | DW20B, DW23B | 25.8 | 655 | 70.4 | 1789 | 31 | 787 | 210.6 | 5349 | 45 875 | 73 58 | 690 252 | 168.2 637 | 21 x 2 | 427 2757 |
| V951121 | 800/65R32 | 30.5LR32 | 178D/181A8 | TL | DW27B | DW25B, DH27B | 30.3 | 770 | 73 | 1853 | 32 | 812 | 218.1 | 5540 | 46 875 | 73 58 | 690 315 | 219.1 830 | 21 x 2 | 509 3282 |
| | 800/70R32 | | 181D/184A8 | | | | New Size in Development | | | | | | | | | | | | | |
| V951138 | 900/60R32 | 35.5LR32 | 181D/184A8 | TL | DW27B | DW28B, DW30B | 33.5 | 850 | 74.5 | 1893 | 32.6 | 828 | 222.9 | 5660 | 46 925 | 72 57 | 772 350 | 257.9 977 | 21 x 2 | 560 3611 |
| | 1050/50R32 | | 170D/178A8 | | | | New Size in Development | | | | | | | | | | | | | |
| | 1250/50R32 | | 194A8/191B | | | | New Size in Development | | | | | | | | | | | | | |

AGRIXTRA H LOAD AND INFLATION

| Metric Size | Standard Size | LI / SS | Service Speed (mph/kph) | TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg) | | | | | | |
|-------------|---------------|------------|-------------------------|---|------------|------------|------------|------------|------------|------------|
| | | | | 15 psi | 18 psi | 20 psi | 23 psi | 26 psi | 29 psi | 32 psi |
| | | | | 1 bar | 1.2 bar | 1.4 bar | 1.6 bar | 1.8 bar | 2 bar | 2.2 bar |
| 1000/50R25 | | 172D/175A8 | 5/10 LT | 11950/5420 | 13210/5990 | 14465/6560 | 15720/7130 | 16460/7465 | 17200/7800 | 17940/8135 |
| | | | 40/65 | 8885/4030 | 9810/4450 | 10750/4875 | 11685/5300 | 12240/5550 | 12790/5800 | 13340/6050 |
| 620/75R26 | 23.1R26 | 166A8/B | 5/10 LT | 8720/3955 | 9450/4285 | 10175/4615 | 10905/4945 | 11545/5235 | 12170/5520 | 12810/5810 |
| | | | 40/65 | 6440/2920 | 6980/3165 | 7510/3405 | 8050/3650 | 8520/3865 | 8985/4075 | 9460/4290 |
| 750/50R26 | | 157D/160A8 | | New Size in Development | | | | | | |
| 750/65R26 | 28LR26 | 166D/169A8 | 5/10 LT | 9855/4470 | 10905/4945 | 11940/5415 | 12975/5885 | 13660/6195 | 14345/6505 | 15025/6815 |
| | | | 40/65 | 7330/3325 | 8105/3675 | 8875/4025 | 9645/4375 | 10155/4605 | 10670/4840 | 11180/5070 |
| 650/75R32 | 24.5R32 | 172D/175A8 | 5/10 LT | 10145/4600 | 11210/5085 | 12280/5570 | 13350/6055 | 14045/6370 | 14750/6690 | 15455/7010 |
| | | | 40/65 | 7540/3420 | 8335/3780 | 9130/4140 | 9925/4500 | 10450/4740 | 10970/4975 | 11500/5215 |
| 800/65R32 | 30.5LR32 | 178D/181A8 | 5/10 LT | 12280/5570 | 13570/6155 | 14875/6745 | 16165/7330 | 16790/7615 | 17420/7900 | 18060/8190 |
| 800/70R32 | | 181D/184A8 | | New Size in Development | | | | | | |
| 900/60R32 | 35.5LR32 | 181D/184A8 | 5/10 LT | 13075/5930 | 14455/6555 | 15820/7175 | 17200/7800 | 18170/8240 | 19130/8675 | 20090/9110 |
| | | | 40/65 | 9725/4410 | 10740/4870 | 11765/5335 | 12790/5800 | 13505/6125 | 14220/6450 | 14940/6775 |
| 1050/50R32 | | 170D/178A8 | | New Size in Development | | | | | | |
| 1250/50R32 | | 194A8/191B | | New Size in Development | | | | | | |

| Metric Size | Standard Size | LI / SS | Service Speed (mph/kph) | TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg) <i>continued</i> | | | | | |
|-------------|---------------|------------|-------------------------|--|------------|-------------|-------------|-------------|-------------|
| | | | | 35 psi | 38 psi | 41 psi | 44 psi | 46 psi | 55 psi |
| | | | | 2.4 bar | 2.6 bar | 2.8 bar | 3 bar | 3.2 bar | 3.8 bar |
| 1000/50R25 | | 172D/175A8 | 5/10 LT | 18685/8475 | | 20835/9450 | | | |
| | | | 40/65 | 13890/6300 | | | | | |
| 620/75R26 | 23.1R26 | 166A8/B | 5/10 LT | 13450/6100 | 14045/6370 | 14640/6640 | 15235/6910 | 15830/7180 | 17530/7950 |
| | | | 40/65 | 9925/4500 | 10365/4700 | 10805/4900 | 11245/5100 | 11685/5300 | |
| 750/50R26 | | 157D/160A8 | | New Size in Development | | | | | |
| 750/65R26 | 28LR26 | 166D/169A8 | 5/10 LT | 15720/7130 | 17530/7950 | | | | |
| | | | 40/65 | 11685/5300 | | | | | |
| 650/75R32 | 24.5R32 | 172D/175A8 | 5/10 LT | 16165/7330 | 16790/7615 | 17420/7900 | 18060/8190 | 18685/8475 | 20835/9450 |
| | | | 40/65 | 12015/5450 | 12490/5665 | 12955/5875 | 13430/6090 | 13890/6300 | |
| 800/65R32 | 30.5LR32 | 178D/181A8 | 5/10 LT | 18685/8475 | 19570/8875 | 20460/9280 | 21355/9685 | 22250/10090 | 24805/11250 |
| | | | 40/65 | 13890/6300 | 14555/6600 | 15215/6900 | 15875/7200 | 16540/7500 | |
| 800/70R32 | | 181D/184A8 | | New Size in Development | | | | | |
| 900/60R32 | 35.5LR32 | 181D/184A8 | 5/10 LT | 21060/9550 | 21905/9935 | 22765/10325 | 23615/10710 | 24465/11095 | 27285/12375 |
| | | | 40/65 | 15655/7100 | 16295/7390 | 16925/7675 | 17565/7965 | 18190/8250 | |
| 1050/50R32 | | 170D/178A8 | | New Size in Development | | | | | |
| 1250/50R32 | | 194A8/191B | | New Size in Development | | | | | |

*LT = Low Torque