

Aggressive R4 tread pattern for applications requiring high traction.

- ▶ Wide tread design for increased flotation
- ▶ Wear and cut-resistant compound
- ▶ Deep undertread for improved puncture resistance
- ▶ Reinforced bead and sidewall for excellent stability



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (LBS/KG)		L.I.
				in	in	32nds	psi	5 mph	25 mph	
				mm	mm	mm	KPa	10 kph	40 kph	
12.5/80-18 (340/80-18)	12	TL	W9	38.7	12.2	33	58	7500	6000	143A8
				983	310	26	400	3405	2725	
	16	TL	W9	38.7	12.2	33	72	8690	6950	148A8
				983	310	26	500	3935	3150	
14.9-24	12	TL	W13	48.2	13.1	31	42	8000	6400	145A8
				1224	333	25	280	3625	2900	
16.9-24	12	TL	W15L	51.5	16.9	33	38	8940	7150	149A8
				1309	429	26	260	4060	3250	
18.4-26	12	TL	W16L	56.1	18.7	35	36	11000	8800	156A8
				1425	475	28	250	5000	4000	
	16	TL	W16L	56.1	18.7	35	45	13125	10500	162A8
				1425	475	28	310	6000	4750	
16.9-28	12	TL	W15L	55.5	16.9	34	38	9815	7850	152A8
				1410	429	27	260	4500	3550	
	14	TL	W15L	55.5	16.9	34	44	10690	8550	155A8
				1410	429	27	300	4875	3875	
18.4-28	12	TL	W16	57.1	17.4	35	36	11375	9100	157A8
				1450	442	28	250	5155	4125	

