



SPECIFICATIONS

# AGRIUMTRA 85 SERIES

## FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
340/85R38	13.6R38	133A8/B	TL	W12	W11	46

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
353	1543	708	4614	750	21 x 2	217

Service Speed (mph/kph)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	4100/1860	4510/2045	4925/2235	5335/2420	5745/2605	6150/2790		6810/3090				
25/40 & 30/50		3330/1510	3640/1650	3935/1785	4245/1925	4540/2060						