



SPECIFICATIONS

# AGRI-MAX 85 SERIES

## FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
420/85R24	16.9R24	137A8/B	TL	W15L	W14L, DW14L, DW15L	46

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
438	1324	583	3959	625	20 x 2	220

Service Speed (mph/kph)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	4585/2080	5040/2285	5500/2495	5950/2700	6415/2910	6865/3115		7605/3450				
25/40 & 30/50		3715/1685	4055/1840	4400/1995	4730/2145	5070/2300						