



SPECIFICATIONS

AGRIXTRA 65 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
440/65R24	-	128D/131A8	TL	W14L	W13, W15L	42

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
442	1182	508	3534	575	18 x 2	195

Service Speed (mph/kph)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)									
	9 psi 0.6 bar	12 psi 0.8 bar	15 psi 1 bar	18 psi 1.2 bar	20 psi 1.4 bar	23 psi 1.6 bar	27 psi 1.9 bar	29 psi 2 bar	32 psi 2.2 bar	35 psi 2.4 bar
5/10 LT	3210/1455	3625/1645	4055/1840	4485/2035	4905/2225	5335/2420	5955/2700			
40/65			3020/1370	3330/1510	3650/1655	3970/1800				