



SPECIFICATIONS

AGRIUMTRA 70 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
480/70R30	-	152D/155A8	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	48

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
483	1478	660	4419	700	19 x 2	282

Service Speed (mph/kph)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)												
	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi
	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar
5/10 LT	5195/2355	5800/2630	6415/2910	7025/3185	7640/3465	8005/3630	8380/3800	8755/3970	9120/4135	9470/4295	9825/4455	10175/4615	10530/4775
40/65		4310/1955	4775/2165	5225/2370	5680/2575	5955/2700	6230/2825	6505/2950	6780/3075	7045/3195	7310/3315	7565/3430	7830/3550