



SPECIFICATIONS

AGRIXTRA

70 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
480/70R34	-	155A8/B	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	48

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
479	1580	711	4724	750	19 x 2	311

Service Speed (mph/ kph)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)													
	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	
	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	
5/10 LT	5975/ 2710	6515/ 2955	7055/ 3200	7595/ 3445	8135/ 3690	8535/ 3870	8930/ 4050	9315/ 4225	9715/ 4405	10175/ 4615	10640/ 4825	11115/ 5040	11575/ 5250	
40/65	4410/ 2000	4805/ 2180	5205/ 2360	5610/ 2545	6010/ 2725	6295/ 2855	6595/ 2990	6880/ 3120	7165/ 3250	7510/ 3405	7860/ 3565	8205/ 3720	8545/ 3875	