

SPECIFICATIONS

AGRIXTRA 65 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
540/65R30	-	150D/153A8	TL	W16L	DW16L, W18L, DW18L	50

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
530	1464	655	4377	700	19 x 2	302

Service Speed (mph/kph)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)									
	9 psi 0.6 bar	12 psi 0.8 bar	15 psi 1 bar	18 psi 1.2 bar	20 psi 1.4 bar	23 psi 1.6 bar	27 psi 1.9 bar	29 psi 2 bar	32 psi 2.2 bar	35 psi 2.4 bar
5/10 LT	4850/ 2200	5490/ 2490	6140/ 2785	6790/ 3080	7430/ 3370	8080/ 3665	8545/ 3875	9005/ 4085	9470/ 4295	9935/ 4505
40/65			4565/ 2070	5050/ 2290	5525/ 2505	6010/ 2725	6350/ 2880	6705/ 3040	7045/ 3195	7385/ 3350