



SPECIFICATIONS

AGRIXTRA XL

FEATURES & BENEFITS:

The Maxam AGRIXTRA XL is a large volume R1W tyre designed specifically for use on high horsepower tractors. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
710/70R38	-	171D/174A8	TL	DW23B	-	62

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
716	1959	870	5857	925	20 x 2	800

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	9425/4275	10685/4845	11950/5420	13210/5990	14465/6560	15720/7130	16350/7415	16980/7700	17605/7985	18235/8270	20340/9225
40/65			8885/4030	9810/4450	10750/4875	11685/5300	12160/5515	12625/5725	13100/5940	13560/6150	