



SPECIFICATIONS

AGRIXTRA XL

FEATURES & BENEFITS:

The Maxam AGRIXTRA XL is a large volume R1W tyre designed specifically for use on high horsepower tractors. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
710/70R42	-	173D/176A8	TL	DW23B	-	62

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
716	2061	921	6162	975	21 x 2	861

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	9965/4520	11290/5120	12625/5725	13945/6325	15280/6930	16605/7530	17275/7835	17940/8135	18610/8440	19285/8745	21500/9750
40/65			9380/4255	10375/4705	11355/5150	12350/5600	12845/5825	13340/6050	13835/6275	14335/6500	