

AGRIXTRA 65



MAXAM MS951R - R1W RADIAL DRIVE TYRE

Extra wide profile 65-series tyre for high flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- Radial tyre construction
- Self-cleaning tread design
- Wide tread for maximized performance in the field
- Low pressure for minimal soil disturbance
- Premium rubber compounds reduce ozone cracking and weathering

Size	LI/SS	Type	Rim (Rec.)	S.W. (mm)	O.D. (mm)	S.L.R. (mm)	R.C. (mm)	S.R.I.	Tread Depth Full (mm)	Tread Depth at Cl (mm)	75% of Int. vol. (l)
650/65R42	165D/168A8	TL	DW20B (DW20A)	645	1912	863	5717	925	58	55	619

Size	LI/SS	Service Speed (km/h)	TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (kg)										
			0.6 bar	0.8 bar	1.0 bar	1.2 bar	1.4 bar	1.6 bar	1.8 (1.9) bar	2.0 bar	2.2 bar	2.4 bar	2.8 bar
650/65R42	165D/168A8	10 km/h Low Torque	3430	3885	4345	4800	5260	5715	6020	6320	6625	6925	7725
		10 km/h High Torque	2935	3325	3715	4105	4495	4890	5145	5405	5665	5925	
		20 km/h		3555	3975	4390	4810	5230	5505	5780	6060	6335	
		25 km/h		3425	3830	4230	4635	5035	5305	5570	5835	6105	
		30 km/h		3325	3715	4105	4495	4890	5145	5405	5665	5925	
		40 km/h		3165	3535	3910	4280	4625	4900	5145	5395	5600	
		50 km/h		3035	3390	3750	4105	4465	4700	4935	5170	5410	
		65 km/h			3230	3570	3910	4250	4475	4700	4925	5150	