

| | Size | Tread Pattern | SW mm | OD mm | SLR mm | RC mm | SRI | Rim | Permitted Rim | Type | Tube |
|----------------|--------------------------|---------------|-------|-------|--------|-------|-------------|-------|---|----------|------------------|
| | 540/65R38 147D | Radial 65 | 530 | 1680 | 760 | 5010 | 800 | DW16L | W15L (°) W16L - W18L DW15L (°) DW18L | TUBELESS | 18.4-38 TR218 |
| Pressure | psi | 9 | 12 | 14 | 17 | 20 | 23 | 26 | 28 | 30 | |
| | bar | 0,6 | 0,8 | 1,0 | 1,2 | 1,4 | 1,6 | 1,8 | 1,9 | 2,1 | |
| Max. Load (kg) | 65 S | 1790 | 2065 | 2345 | 2590 | 2835 | 3080 | | | | |
| | 50 S | 1880 | 2170 | 2460 | 2720 | 2980 | 3235 | | | | |
| | 40 S | 1960 | 2260 | 2565 | 2835 | 3105 | 3375 | | | | |
| | 30 S | 2055 | 2375 | 2695 | 2980 | 3260 | 3545 | | | | |
| | 10 LT S | 2430 | 2810 | 3185 | 3520 | 3855 | 4190 | 4480 | 4620 | 5240 | |
| | 10 HT S | 2055 | 2375 | 2695 | 2980 | 3260 | 3545 | | | | |