

	Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rim	Type	Tube
	<b>360/70R24</b> 122A8 122B	<b>Radial 70</b>	<b>352</b>	<b>1152</b>	<b>518</b>	<b>3455</b>	<b>550</b>	<b>W11</b>	<b>W10-W12</b> <b>DW10-DW11</b> <b>DW12</b>	<b>TUBELESS</b>	<b>13.6-24</b> <b>TR218</b>
Pressure	<b>psi</b>	<b>6</b>	<b>9</b>	<b>12</b>	<b>14</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>30</b>
	<b>bar</b>	<b>0,4</b>	<b>0,6</b>	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>1,9</b>	<b>2,1</b>
Max. Load (kg)	50 S		825	960	1095	1230	1365	1500			
	<b>40 S</b>		825	960	1095	1230	1365	<b>1500</b>			
	30 S		885	1025	1170	1315	1460	1605			
	10 LT S	920	1120	1305	1490	1675	1855	2040	2185	2245	2550
	10 HT S		885	1025	1170	1315	1460	1605			