

	Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rim	Type	Tube
	<b>380/85R30</b> 135A8 132B (14.9R30)	<b>Radial 85</b>	<b>385</b>	<b>1400</b>	<b>625</b>	<b>4180</b>	<b>675</b>	<b>W13</b>	<b>W12-W11 DW11-DW12 DW13</b>	<b>TUBELESS</b>	<b>14.9-30 TR218</b>
Pressure	<b>psi</b>	<b>6</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>30</b>
	<b>bar</b>	<b>0,4</b>	<b>0,6</b>	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>1,9</b>	<b>2,1</b>
Max. Load (kg)	50 S		1305	1440	1575	1715	1850	2000			
	<b>40 S</b>		1430	1580	1730	1880	2030	<b>2180</b>			
	30 S		1535	1695	1855	2015	2175	2335			
	10 LT	1745	1950	2155	2360	2565	2770	2970	3170	3270	3710
	10 HT		1535	1695	1855	2015	2175	2335			