

	Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rim	Type	Tube
	<b>420/85R24</b> 137A8 134B (16.9R24)	<b>Radial 85</b>	<b>445</b>	<b>1310</b>	<b>585</b>	<b>3925</b>	<b>625</b>	<b>W15L</b>	<b>W14L DW14L DW15L</b>	<b>TUBELESS</b>	<b>16.9-24 TR218</b>
Pressure	<b>psi</b>	<b>6</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>30</b>
	<b>bar</b>	<b>0,4</b>	<b>0,6</b>	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>1,9</b>	<b>2,1</b>
Max. Load (kg)	50 S		1385	1530	1670	1815	1955	2120			
	<b>40 S</b>		1520	1680	1835	1990	2145	<b>2300</b>			
	30 S		1630	1800	1965	2130	2300	2465			
	10 LT	1840	2055	2270	2485	2700	2915	3130	3345	3450	3910
	10 HT		1630	1800	1965	2130	2300	2465			