

	Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rim	Type	Tube
	<b>420/85R28</b> 139A8 136B (16.9R28)	<b>Radial 85</b>	<b>445</b>	<b>1405</b>	<b>625</b>	<b>4200</b>	<b>675</b>	<b>W15L</b>	<b>W14L DW14L DW15L</b>	<b>TUBELESS</b>	<b>16.9-28 TR218</b>
Pressure	<b>psi</b>	<b>6</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>30</b>
	<b>bar</b>	<b>0,4</b>	<b>0,6</b>	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>1,9</b>	<b>2,1</b>
Max. Load (kg)	50 S		1465	1615	1765	1915	2065	2240			
	<b>40 S</b>		1605	1770	1935	2100	2265	<b>2430</b>			
	30 S		1720	1895	2075	2250	2425	2605			
	10 LT	1955	2185	2410	2635	2860	3085	3310	3535	3645	4135
	10 HT		1720	1895	2075	2250	2425	2605			