

	Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rim	Type	Tube
	<b>460/85R34</b> 147A8 144B (18.4R34)	<b>Radial 85</b>	<b>485</b>	<b>1640</b>	<b>725</b>	<b>4915</b>	<b>775</b>	<b>W16L</b>	<b>W15L DW15L DW16L</b>	<b>TUBELESS</b>	<b>18.4-34 TR218</b>
Pressure	<b>psi</b>	<b>6</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>30</b>
	<b>bar</b>	<b>0,4</b>	<b>0,6</b>	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>1,9</b>	<b>2,1</b>
Max. Load (kg)	50 S		1845	2035	2225	2420	2610	2800			
	<b>40 S</b>		2025	2235	2445	2655	2865	<b>3075</b>			
	30 S		2170	2395	2620	2845	3070	3295			
	10 LT	2465	2755	3045	3335	3620	3905	4190	4475	4615	5230
	10 HT		2170	2395	2620	2845	3070	3295			