

	Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rim	Type	Tube
	<b>420/70R28</b> 133A8 133B	<b>Radial 70</b>	<b>423</b>	<b>1354</b>	<b>605</b>	<b>4060</b>	<b>650</b>	<b>W13</b>	<b>W12-W14L DW12-DW13 DW14L</b>	<b>TUBELESS</b>	<b>16.9-28 TR218</b>
Pressure	psi	<b>6</b>	<b>9</b>	<b>12</b>	<b>14</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>30</b>
	bar	<b>0,4</b>	<b>0,6</b>	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>1,9</b>	<b>2,1</b>
Max. Load (kg)	50 S		1135	1320	1505	1690	1875	2060			
	<b>40 S</b>		1135	1320	1505	1690	1875	<b>2060</b>			
	30 S		1210	1410	1610	1805	2005	2205			
	10 LT S	1260	1540	1795	2045	2295	2550	2800	3000	3080	3500
	10 HT S		1210	1410	1610	1805	2005	2205			