



Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

Applications

Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE (bar)	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)			30KMPH (Kgs)	40KMPH (Kgs)	
10.0/80-12	8	TT/TL	9.0	7.0	710	264	312	2080	116A6/112A8	1250	1120	3.1	122A6/119A8	1500	1360	3.7
10.0/80-12	10	TT/TL	9.0	7.0	710	264	312	2080	121A6/118A8	1450	1320	3.9	127A6/123A8	1750	1550	4.7
10.0/80-12	12	TT/TL	9.0	7.0	710	264	312	2080	124A6/120A8	1600	1400	4.4	130A6/126A8	1900	1700	5.3
10.0/80-12	14	TT/TL	9.0	7.0	710	264	312	2080	126A6/123A8	1700	1550	5.2	131A6/127A8	1950	1750	6.2
10.0/75-15.3	8	TT/TL	9.0	-	760	264	343	2227	119A6/115A8	1360	1215	3.1	124A6/120A8	1600	1400	3.7
10.0/75-15.3	10	TT/TL	9.0	-	760	264	343	2227	123A6/119A8	1550	1360	3.9	129A6/125A8	1850	1650	4.7
10.0/75-15.3	12	TT/TL	9.0	-	760	264	343	2227	126A6/122A8	1700	1500	4.7	132A6/128A8	2000	1800	5.6
10.0/75-15.3	14	TT/TL	9.0	-	760	264	343	2227	130A6/126A8	1900	1700	5.5	136A6/132A8	2240	2000	6.6
10.0/75-15.3	16	TT/TL	9.0	-	760	264	343	2227	134A8/130A6	2120	1900	6.2	140A6/136A8	2500	2240	7.8
10.0/75-15.3	18	TT/TL	9.0	-	760	264	343	2227	138A6/134A8	2360	2120	6.5	144A6/140A8	2800	2500	7.8
10.0/75-15.3	22	TT/TL	9.0	-	760	264	343	2227	142A6/138A8	2650	2360	7.1	148A6/144A8	3150	2800	8.5
11.5/80-15.3	10	TT/TL	9.0	-	845	290	343	2473	131A6/127A8	1950	1750	3.4	137A6/133A8	2300	2060	4.1
11.5/80-15.3	12	TT/TL	9.0	-	845	290	343	2473	135A6/131A8	2180	1950	4.1	141A6/137A8	2575	2300	4.9
11.5/80-15.3	14	TT/TL	9.0	-	845	290	343	2473	139A6/135A8	2430	2180	4.8	145A6/141A8	2900	2575	5.7
11.5/80-15.3	16	TT/TL	9.0	-	845	290	343	2473	141A6/137A8	2575	2300	5.4	147A6/143A8	3075	2725	6.5
11.5/80-15.3	18	TT/TL	9.0	-	845	290	343	2473	143A6/139A8	2725	2430	5.4	149A6/145A8	3250	2900	7.1
11.5/80-15.3	22	TT/TL	9.0	-	845	290	343	2473	145A6/141A8	2900	2575	6.3	151A6/147A8	3450	3075	7.3
12.5/80-15.3	8	TT/TL	9.0	-	889	307	387	2591	130A6/126A8	1900	1700	2.7	136A6/132A8	2240	2000	3.3
12.5/80-15.3	10	TT/TL	9.0	-	889	307	387	2591	135A6/131A8	2180	1950	3.1	141A6/137A8	2575	2300	3.7
12.5/80-15.3	12	TT/TL	9.0	-	889	307	387	2591	139A6/135A8	2430	2180	3.7	145A6/141A8	2900	2575	4.4
12.5/80-15.3	14	TT/TL	9.0	-	889	307	387	2591	142A6/138A8	2650	2360	4.3	148A6/144A8	3150	2800	5.2
12.5/80-15.3	16	TT/TL	9.0	-	889	307	387	2591	144A6/140A8	2800	2500	4.9	150A6/146A8	3350	3000	5.9
12.5/80-15.3	22	TT/TL	9.0	-	889	307	387	2591	150A6/146A8	3350	3000	6.0	156A6/152A8	4000	3550	7.2