



## Salient Features

- Unique lug design with multiple bends for extra surface for higher mileage.
- Extra wide design for heavy duty forklifts and equipments.
- Stronger and tougher body plies for extra load carrying capacity.
- Cuts and cracks resistant tread compound for longer service life.

## Applications

Forklift

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	MAX. LOAD		PRESSURE (bar)
			REC.INCH	ALT.INCH				10KMPH(Kgs)	25KMPH(Kgs)	
18x7-8	10	TT	4.33 R	5.00F	470	173	119A2/116A5	1360	1250	8.0
18x7-8	12	TT	4.33 R	5.00F	470	173	121A2/119A5	1450	1360	8.5
18x7-8	14	TT	4.33 R	5.00F	470	173	123A2/121A5	1550	1450	9.0
18x7-8	16	TT	4.33 R	5.00F	470	173	128A2/125A5	1850	1650	10.0
4.00-8	10	TT	3.25I	3.00D	414	115	100A2/97A5	800	730	10.0
5.00-8	8	TT	3.0D	3.25 I	467	135	109A2/106A5	1030	950	8.3
5.00-8	10	TT	3.0D	3.25 I	467	135	114A2/111A5	1180	1090	10.0
5.00-8	12	TT	3.0D	3.25 I	467	135	117A2/114A5	1285	1180	10.5
6.00-9	10	TT	4.00E	-	544	158	121A2/118A5	1450	1320	8.5
6.00-9	12	TT	4.00E	-	544	158	123A2/121A5	1550	1450	10.0
6.50-10	10	TT	5.00F	5.50F	595	185	124A2/122A5	1600	1500	7.8
6.50-10	12	TT	5.00F	5.50F	595	185	128A2/125A5	1800	1650	9.0
6.50-10	14	TT	5.00F	5.50F	595	185	131A2/128A5	1950	1800	10.0
7.00-12	12	TT	5.00S	-	695	188	136A2/133A5	2240	2060	8.5
7.00-12	14	TT	5.00S	-	695	188	137A2/134A5	2300	2120	9.0
7.00-12	16	TT	5.00S	-	695	188	139A2/136A5	2430	2240	10.0
8.25-15	12	TT	6.5	7	853	236	149A2/146A5	3250	3000	7.0
8.25-15	14	TT	6.5	7	853	236	152A2/149A5	3550	3250	8.0
8.25-15	16	TT	6.5	7	853	236	155A2/152A5	3875	3550	9.3
8.15-15	12	TT	7	7.0BD	722	215	145A2/142A5	2900	2650	8.3
8.15-15	14	TT	7	7.0BD	722	215	148A2/145A5	3150	2900	9.0
8.15-15	16	TT	7	7.0BD	722	215	152A2/149A5	3550	3250	10.5

