



## Salient Features

- Good Traction in all weather conditions.
- Good self-cleaning properties.
- Strong and sturdy heavy duty nylon plies for longer service durability.
- Cuts and cracks resistant tread compound for increased service life.

## Applications

Backhoe

Dozer

Grader

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	PRESSURE
			REC.INCH	ALT.INCH						(Kgs)	(bar)
13.00-24	12	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC)	1278	333	582.186	3785	143A8	2725	3.0
13.00-24	14	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC)	1278	333	582.186	3785	146A8	3000	3.5
13.00-24	16	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC)	1278	333	582.186	3785	148A8	3150	4
14.00-24	12	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	147A8	3075	2.8
14.00-24	14	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	151A8	3450	3.3
14.00-24	16	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	153A8	3650	3.8
14.00-24	20	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	157A8	4125	4
14.00-24	24	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	160A8	4500	4.5