



Salient Features

- 80% Field & 20% Road usage
- Mainly for field usage
- Tread pattern featuring self-cleaning properties
- Less impact on soil fertility, preserving value of crops

Applications

Baler

Trailer

SIZES

SIZE	O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	RIM		Bar KM/H	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
					REC.INCH	ALT.INCH									
600/55R26.5 176A8/165D	1346	625	606	3971	AG20	-	65	2165	2630	3040	3505	3970	4275	4740	5150
							50	2620	3180	3680	4240	4805	5180	5740	6235
							40	2985	3625	4190	4830	5470	5895	6535	7100
							25	3420	4155	4805	5540	6270	6760	7490	8140
							10	3895	4730	5470	6305	7140	7695	8530	9270
560/60R22.5 175A8/164D	1244	565	560	3670	AG 16	17.00,20.00	65	2110	2564	2959	3425	3876	4167	4604	5000
							50	2553	3103	3580	4144	4690	5042	5571	6050
							40	2911	3538	4083	4726	5349	5750	6354	6900
							25	3333	4051	4675	5411	6124	6583	7274	7900
							10	3797	4615	5325	6164	6977	7500	8287	9000