



# Nokian EL5 Radial 600/55R26.5 – T445146

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI / SS	Pattern	TT / TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Maximum inflation pressure		Load capacity kg / lbs				Total tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	40 km/h	25 mph	65 km/h	40 mph	mm	32 nds in
Ø T445146	600/55R26.5	158 D	ELS	TL	AG 20.00	20.00	600	23.6	1 333	52.5	603	23.7	4 040	159.1	320	46	5 780	12 745	4 250	9 370	22	28

⊗ Production ended

## LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

Constant		0.8 bar	12 psi	1.2 bar	17 psi	1.6 bar	23 psi	2.0 bar	29 psi	2.4 bar	35 psi	2.8 bar	41 psi	3.2 bar	46 psi
km/h	mph	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
10	5	3 240	7 145	4 040	8 905	4 920	10 845	5 540	12 215	6 400	14 110	7 200	15 875	7 650	16 865
20	12.5	2 970	6 550	3 700	8 155	4 500	9 920	5 080	11 200	5 860	12 920	6 600	14 550	7 050	15 540
25	15	2 850	6 285	3 540	7 805	4 320	9 525	4 860	10 715	5 620	12 390	6 350	14 000	6 750	14 880
30	20	2 720	5 995	3 400	7 495	4 120	9 085	4 660	10 275	5 380	11 860	6 050	13 340	6 450	14 220
40	25	2 450	5 400	3 060	6 745	3 720	8 200	4 200	9 260	4 840	10 670	5 440	11 995	5 780	12 745
50	30	2 180	4 805	2 710	5 975	3 300	7 275	3 740	8 245	4 300	9 480	4 840	10 670	5 160	11 375
65	40	1 800	3 970	2 240	4 940	2 725	6 010	3 075	6 780	3 550	7 825	4 000	8 820	4 250	9 370

## LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl <sub>2</sub> )		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
475	125	355	95	292	75	149	330	441	970

## TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55098	TR 218 A