



# Nokian EL S Radial SB 750/55R26.5 – T445601

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI / SS	Pattern	TT / TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Maximum inflation pressure		Load capacity kg / lbs				Total tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	40 km/h	25 mph	65 km/h	40 mph	mm	32 nds in
T445601	750/55R26.5	177 D	ELS SB <sup>3)</sup>	TL	AG 24.00	-	750	30	1 498	59.0	663	26.1	4 555	179.3	400	58	9 930	21 845	7 300	16 060	24	30

3) SB = steel belted

## LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

Constant		0.8 bar	12 psi	1.2 bar	17 psi	1.6 bar	23 psi	2.0 bar	29 psi	2.4 bar	35 psi	2.8 bar	41 psi	3.2 bar	46 psi	3.6 bar	53 psi	4.0 bar	58 psi
km/h	mph	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
10	6	4 140	9 110	5 400	11 880	6 570	14 455	7 425	16 335	8 775	19 305	9 810	21 580	10 800	23 760	11 700	25 740	13 140	28 910
20	12	3 795	8 350	4 950	10 890	6 025	13 255	6 805	14 970	8 045	17 700	8 995	19 790	9 900	21 780	10 725	23 595	12 045	26 500
25	16	3 635	7 995	4 740	10 430	5 765	12 685	6 520	14 345	7 705	16 950	8 610	18 940	9 480	20 855	10 270	22 595	11 535	25 375
30	19	3 475	7 645	4 530	9 965	5 510	12 120	6 230	13 705	7 360	16 190	8 230	18 105	9 060	19 930	9 815	21 595	11 025	24 255
40	25	3 130	6 885	4 080	8 975	4 965	10 925	5 610	12 340	6 630	14 585	7 410	16 300	8 160	17 950	8 840	19 450	9 930	21 845
50	31	2 785	6 125	3 630	7 985	4 415	9 715	4 990	10 980	5 900	12 980	6 595	14 510	7 260	15 970	7 865	17 305	8 835	19 435
65	40	2 300	5 060	3 000	6 600	3 650	8 030	4 125	9 075	4 875	10 725	5 450	11 990	6 000	13 200	6 500	14 300	7 300	16 060

## LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl <sub>2</sub> )		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
795	210	596	158	489	129	249	549	739	1 625

## TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55102	TR 218 A