



## Nokian Country King 560/60R22.5 – T445401

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI / SS	Pattern	TT / TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Maximum inflation pressure		Load capacity kg / lbs				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	40 km/h	25 mph	65 km/h	40 mph	mm	32 nds in	mm	32 nds in
T445401	560/60R22.5	161 D	Country King	TL	AG 16.00	15.00, 16.00, 17.00, 20.00	564	22.2	1 244	49.0	557	21.9	3 764	148.2	400	58	6 300	13 890	4 625	10 195	18	23	15	19

### LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

Constant		0.8 bar	12 psi	1.2 bar	17 psi	1.6 bar	23 psi	2.0 bar	29 psi	2.4 bar	35 psi	2.8 bar	41 psi	3.2 bar	46 psi	3.6 bar	53 psi	4.0 bar	58 psi
km/h	mph	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
10	5	2 970	6 550	3 720	8 200	4 380	9 655	5 040	11 110	5 680	12 520	6 400	14 110	7 000	15 430	7 650	16 865	8 350	18 410
20	12.5	2 730	6 020	3 400	7 495	4 020	8 860	4 620	10 185	5 200	11 465	5 860	12 920	6 400	14 110	7 050	15 540	7 650	16 865
25	15	2 610	5 755	3 260	7 185	3 840	8 465	4 440	9 790	4 980	10 980	5 620	12 390	6 150	13 560	6 750	14 880	7 350	16 205
30	20	2 500	5 510	3 120	6 880	3 680	8 115	4 240	9 350	4 760	10 495	5 380	11 860	5 860	12 920	6 450	14 220	7 000	15 430
40	25	2 250	4 960	2 810	6 195	3 320	7 320	3 820	8 420	4 300	9 480	4 840	10 670	5 280	11 640	5 780	12 745	6 300	13 890
50	30	2 000	4 410	2 500	5 510	2 940	6 480	3 400	7 495	3 820	8 420	4 300	9 480	4 700	10 360	5 160	11 375	5 600	12 345
65	40	1 650	3 640	2 060	4 540	2 430	5 355	2 800	6 175	3 150	6 945	3 550	7 825	3 875	8 545	4 250	9 370	4 625	10 195

### LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
390	105	295	80	240	65	122	270	362	800

### TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55089	TR 218 A