



Nokian Country King 650/50R22.5 – T445407

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI / SS	Pattern	TT / TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Maximum inflation pressure		Load capacity kg / lbs				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	40 km/h	25 mph	65 km/h	40 mph	mm	32 nds in	mm	32 nds in
T445407	650/50R22.5	163 D	Country King	TL	AG 20.00	20.00	645	25.4	1 237	48.7	564	22.2	3 789	149.2	400	58	6 650	14 660	4 875	10 745	18	23	15	19

LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

Constant		0.8 bar	12 psi	1.2 bar	17 psi	1.6 bar	23 psi	2.0 bar	29 psi	2.4 bar	35 psi	2.8 bar	41 psi	3.2 bar	46 psi	3.6 bar	53 psi	4.0 bar	58 psi
km/h	mph	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
10	5	3 160	6 965	3 940	8 685	4 780	10 540	5 400	11 905	6 050	13 340	7 000	15 430	7 450	16 425	8 100	17 855	8 800	19 400
20	12.5	2 890	6 370	3 600	7 935	4 380	9 655	4 960	10 935	5 540	12 215	6 400	14 110	6 850	15 100	7 450	16 425	8 050	17 745
25	15	2 770	6 105	3 460	7 630	4 200	9 260	4 740	10 450	5 300	11 685	6 150	13 560	6 550	14 440	7 150	15 765	7 750	17 085
30	20	2 650	5 840	3 300	7 275	4 020	8 860	4 540	10 010	5 060	11 155	5 860	12 920	6 250	13 780	6 800	14 990	7 400	16 315
40	25	2 380	5 245	2 970	6 550	3 620	7 980	4 080	8 995	4 560	10 055	5 280	11 640	5 620	12 390	6 150	13 560	6 650	14 660
50	30	2 120	4 675	2 640	5 820	3 220	7 100	3 640	8 025	4 060	8 950	4 700	10 360	5 000	11 025	5 460	12 035	5 900	13 005
65	40	1 750	3 860	2 180	4 805	2 650	5 840	3 000	6 615	3 350	7 385	3 875	8 545	4 125	9 095	4 500	9 920	4 875	10 745

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
460	120	345	90	283	75	144	315	427	940

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55089	TR 218 A