



Nokian Forest King ELS L-2 600/50-22.5 16PR – T486034

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure for load capacity calculation		Max. Inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
									mm	in	mm	in	mm	in	mm	in	kPa	psi	kPa	psi	mm	32 nds in	mm	32 nds in
T486034	600/50-22.5	149 A8 / 156 A2	16	ELS L-2	SF	TT	AG 20.00		600	23.6	1 171	46.1	531	20.9	3 522	138.7	320	46	430	62	32	40	-	-

Production ended

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	2 120	4 675	2 120	4 675	2 575	5 675	2 575	5 675
200	29	2 430	5 355	2 430	5 355	3 000	6 615	3 000	6 615
240	35	2 725	6 010	2 725	6 010	3 350	7 385	3 350	7 385
280	41	3 000	6 615	3 000	6 615	3 650	8 045	3 650	8 045
320	46	3 250	7 165	3 250	7 165	4 000	8 820	4 000	8 820

Maximum inflation pressure 430 kPa, without increase to the above load capacity values.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
350	90	265	70	215	55	110	245	325	715

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55089	TR 218 A