



Nokian Forest King ELS L-2 650/65-26.5 20PR – T486066

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure for load capacity calculation		Max. Inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
									mm	in	mm	in	mm	in	mm	in	kPa	psi	kPa	psi	mm	32 nds in	mm	32 nds in
T486066	650/65-26.5	174 A8 / 181 A2	20	ELS L-2	SF	TT	AG 20.00		650	25.6	1 485	58.5	674	26.5	4 461	175.6	500	73	550	80	35	44	32	40

⊗ Production ended

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	3 250	7 165	3 480	7 670	4 000	8 820	4 000	8 820
200	29	3 750	8 265	4 010	8 840	4 625	10 195	4 625	10 195
240	35	4 250	9 370	4 550	10 030	5 300	11 685	5 300	11 685
280	41	4 625	10 195	4 950	10 915	5 600	12 345	5 600	12 345
320	46	5 000	11 025	5 350	11 795	6 150	13 560	6 150	13 560
360	52	5 300	11 685	5 670	12 500	6 500	14 330	6 500	14 330
400	58	5 600	12 345	5 990	13 205	6 900	15 210	6 900	15 210
450	65	6 150	13 560	6 580	14 505	7 500	16 535	7 500	16 535
500	73	6 700	14 770	7 170	15 805	8 250	18 190	8 250	18 190

Maximum inflation pressure 550 kPa, without increase to the above load capacity values.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
585	155	440	115	360	95	184	405	544	1 200

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55102	TR 218 A