



Nokian Forest King TRS 2 600/55-26.5 20PR – T445567

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure for load capacity calculation		Max. Inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
									mm	in	mm	in	mm	in	mm	in	mm	in	kPa	psi	kPa	psi	mm	32 nds in
T445567	600/55-26.5	165 A8 / 172 A2	20	TRS 2	SF	TT	AG 20.00		601	23.7	1 340	52.8	619	24.4	4 096	161.3	500	73	550	80	48	61	-	-

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	2 500	5 510	2 680	5 910	3 075	6 780	3 075	6 780
200	29	2 800	6 175	3 000	6 615	3 450	7 605	3 450	7 605
240	35	3 150	6 945	3 370	7 430	3 875	8 545	3 875	8 545
280	41	3 450	7 605	3 690	8 135	4 250	9 370	4 250	9 370
320	46	3 750	8 265	4 010	8 840	4 625	10 195	4 625	10 195
360	52	4 000	8 820	4 280	9 435	4 875	10 745	4 875	10 745
400	58	4 250	9 370	4 550	10 030	5 300	11 685	5 300	11 685
450	65	4 625	10 195	4 950	10 915	5 600	12 345	5 600	12 345
500	73	5 150	11 355	5 510	12 145	6 300	13 890	6 300	13 890

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
386	100	290	75	238	65	121	265	359	790

Maximum inflation pressure 550 kPa, without increase to the above load capacity values.

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55098	TR 218 A