



Nokian Forest King TRS L-2 650/60-26.5 20PR – T445395

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure for load capacity calculation		Max. Inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
									mm	in	mm	in	mm	in	mm	in	kPa	psi	kPa	psi	mm	32 nds in	mm	32 nds in
T445395	650/60-26.5	172 A8 / 179 A2	20	TRS L-2	SF	TT	AG 20.00		650	25.6	1 485	58.5	676	26.6	4 467	175.9	500	73	550	80	50	63	42	53

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	3 075	6 780	3 290	7 255	3 750	8 265	3 750	8 265
200	29	3 450	7 605	3 690	8 135	4 250	9 370	4 250	9 370
240	35	3 875	8 545	4 150	9 150	4 750	10 470	4 750	10 470
280	41	4 250	9 370	4 550	10 030	5 300	11 685	5 300	11 685
320	46	4 625	10 195	4 950	10 915	5 600	12 345	5 600	12 345
360	52	4 875	10 745	5 220	11 510	6 000	13 230	6 000	13 230
400	58	5 150	11 355	5 510	12 145	6 300	13 890	6 300	13 890
450	65	5 800	12 785	6 210	13 690	7 100	15 655	7 100	15 655
500	73	6 300	13 890	6 740	14 860	7 750	17 085	7 750	17 085

Maximum inflation pressure 550 kPa, without increase to the above load capacity values.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs		
550	145	415	110	338	90	173	380	511	1 125

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55102	TR 218 A