



## Nokian Forest King TRS LS-2 23.1-26 16PR – T486510

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Width		Diameter		Loaded static radius		Rolling circumference		10 km/h / 5 mph				30 km/h / 20 mph				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	Load capacity*		Inflation pressure		Load capacity*		Inflation pressure		mm	32 nds in	mm	32 nds in
															kg	lbs	kPa	psi	kg	lbs	kPa	psi				
T486510	23.1-26	16	TRS LS-2	SF	TT	DW20B	587	23.1	1 632	64.3	736	29.0	4 857	191.2	6 300	13 890	280	41	4 500	9 920	240	35	54	68	51	64

⊘ Production ended

\*) Note! The load capacity of imperial sizes is according to the old method of calculation (STRO).

### LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
655	175	490	130	403	106	205	450	609	1345

### TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55102	TR 218 A