



# Nokian Forest King TRS LS-2 24.5-32 16PR – T486800

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Width		Diameter		Loaded static radius		Rolling circumference		10 km/h / 5 mph				30 km/h / 20 mph				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	Load capacity*		Inflation pressure		Load capacity*		Inflation pressure		mm	32 nds in	mm	32 nds in
															kg	lbs	kPa	psi	kg	lbs	kPa	psi				
Ø T486800	24.5-32	16	TRS LS-2	SF	TT	DH21	622	24.5	1 831	72.1	825	32.5	5 397	212.5	7 000	15 430	240	35	5 000	11 025	210	30				

Ø Production ended

\*) **Note!** The load capacity of imperial sizes is according to the old method of calculation (STRO).

## LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
l	gal (US)	l	gal (US)	Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
				l	gal (US)	kg	lbs	kg	lbs
835	220	625	165	514	136	262	580	776	1 710

## TUBES AND VALVES

Tube product code	Valve tube-type
T55393	TR 218 A