



Nokian Forest King TRS LS-2 28L-26 26PR – T445516

SF = STEEL FORTIFIED

TL = TUBELESS, may be fitted with or without tube

Product code	Size	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Width		Diameter		Loaded static radius		Rolling circumference		10 km/h / 5 mph				30 km/h / 20 mph				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	Load capacity*		Inflation pressure		Load capacity*		Inflation pressure		mm	32 nds in	mm	32 nds in
															kg	lbs	kPa	psi	kg	lbs	kPa	psi				
T445516	28L-26	26	TRS LS-2	SF	TL	DW25B	714	28.1	1 644	64.7	733	28.9	4 945	194.7	9 200	20 280	400	58	6 550	14 440	340	49	53	67	49	62

***) Note!** The load capacity of imperial sizes is according to the old method of calculation (STRO).

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
l	gal (US)	l	gal (US)	Water		Salt (CaCl ₂)		Total weight increase	
				l	gal (US)	kg	lbs	kg	lbs
800	210	600	160	492	130	251	555	743	1 640

TUBES AND VALVES

Tube product code	Valve tube-type
T55101	TR 218 A