



Nokian Forest King TRS LS-2 30.5L-32 20PR – T445529

SF = STEEL FORTIFIED

TL = TUBELESS, may be fitted with or without tube

Product code	Size	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Width		Diameter		Loaded static radius		Rolling circumference		10 km/h / 5 mph				30 km/h / 20 mph				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	Load capacity*		Inflation pressure		Load capacity*		Inflation pressure		mm	32 nds in	mm	32 nds in
															kg	lbs	kPa	psi	kg	lbs	kPa	psi				
Ø T445529	30.5L-32	20	TRS LS-2	SF	TL	DH 27	795	31.3	1 853	73.0	824	32.4	5 492	216.2	8 400	18 520	240	35	6 000	13 230	210	30	57	72	54	68

Ø Production ended

*) **Note!** The load capacity of imperial sizes is according to the old method of calculation (STRO).

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
l	gal (US)	l	gal (US)	Water		Salt (CaCl ₂)		Total weight increase	
				l	gal (US)	kg	lbs	kg	lbs
1 090	290	820	215	671	177	342	755	1 013	2 235

TUBES AND VALVES

Tube product code	Valve tube-type
T55388	TR 218 A