



Nokian Forest King TRS LS-2 30.5L-32 26PR – T445515

SF = STEEL FORTIFIED

TL = TUBELESS, may be fitted with or without tube

| Product code | Size | PR | Pattern Forest King | Steel fortified | TT/TL | Rim | Width | | Diameter | | Loaded static radius | | Rolling circumference | | 10 km/h / 5 mph | | | | 30 km/h / 20 mph | | | | Total tread depth | | Tread depth measured on top of tie-bar | |
|--------------|----------|----|---------------------|-----------------|-------|-------|-------|------|----------|------|----------------------|------|-----------------------|-------|-----------------|--------|--------------------|-----|------------------|--------|--------------------|-----|-------------------|-----------|--|-----------|
| | | | | | | | mm | in | mm | in | mm | in | mm | in | Load capacity* | | Inflation pressure | | Load capacity* | | Inflation pressure | | mm | 32 nds in | mm | 32 nds in |
| | | | | | | | | | | | | | | | kg | lbs | kPa | psi | kg | lbs | kPa | psi | | | | |
| ☞ T445515 | 30.5L-32 | 26 | TRS LS-2 | SF | TL | DH 27 | 795 | 31.3 | 1 853 | 73.0 | 823 | 32.4 | 5 510 | 216.9 | 10 000 | 22 045 | 310 | 45 | 7 100 | 15 655 | 280 | 41 | 57 | 72 | 54 | 68 |

☞ Production ended

 *) **Note!** The load capacity of imperial sizes is according to the old method of calculation (STRO).

LIQUID AND SALT BALLASTING

| Tire volume 100% | | Water filling (75%) | | Water / salt filling (75% / -30°C / -22°F) | | | | | |
|------------------|----------|---------------------|----------|--|----------|---------------------------|-----|-----------------------|-------|
| l | gal (US) | l | gal (US) | Water | | Salt (CaCl ₂) | | Total weight increase | |
| | | | | l | gal (US) | kg | lbs | kg | lbs |
| 1 090 | 290 | 820 | 215 | 671 | 177 | 342 | 755 | 1 013 | 2 235 |

TUBES AND VALVES

| Tube product code | Valve tube-type |
|-------------------|-----------------|
| T55388 | TR 218 A |