



Nokian Forest King TRS LS-2 35.5L-32 26PR – T445539

SF = STEEL FORTIFIED

TL = TUBELESS, may be fitted with or without tube

Product code	Size	PR	Pattern Forest King	Steel fortified	TT/TL	Rim	Width		Diameter		Loaded static radius		Rolling circumference		10 km/h / 5 mph				30 km/h / 20 mph				Total tread depth		Tread depth measured on top of tie-bar	
							mm	in	mm	in	mm	in	mm	in	Load capacity*		Inflation pressure		Load capacity*		Inflation pressure		mm	32 nds in	mm	32 nds in
															kg	lbs	kPa	psi	kg	lbs	kPa	psi				
Ø T445539	35.5L-32**	26	TRS LS-2	SF	TL	DH 31	902	35.5	2 011	79.2	901	35.5	6 026	237.2	12 150	26 785	280	41	8 750	19 290	240	35	57	72	54	68

Ø Production ended

*) **Note!** The load capacity of imperial sizes is according to the old method of calculation (STRO).

***) **Note!** New pattern.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
l	gal (US)	l	gal (US)	Water		Salt (CaCl ₂)		Total weight increase	
				l	gal (US)	kg	lbs	kg	lbs
1 490	395	1 120	295	917	242	467	1 030	1 384	3 050

TUBES AND VALVES

Tube product code	Valve tube-type
-------------------	-----------------

For 35.5L-32
Nokian tube not available