



Nokian Forest Rider 600/50R24.5 – T445472

SB = STEEL BELTED TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern Forest	Steel belted	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Max inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	mm	32 nds in	mm	32 nds in
☞ T445472	600/50R24.5	164 A8 / 171 A2	Rider	SB	TL	AG 20.00	-	600	23.6	1 230	48.4	563	22.2	3 726	146.7	550	80	45	57	39	49

☞ Production ended

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	1 980	4 365	2 180	4 805	2 330	5 135	2 680	5 910	2 650	5 840
200	29	2 280	5 025	2 500	5 510	2 680	5 910	3 080	6 790	3 075	6 780
240	35	2 550	5 620	2 800	6 175	3 000	6 615	3 440	7 585	3 450	7 605
280	41	2 800	6 175	3 075	6 780	3 290	7 255	3 780	8 335	3 750	8 265
320	46	3 050	6 725	3 350	7 385	3 580	7 890	4 120	9 085	4 125	9 095
360	52	3 230	7 120	3 550	7 825	3 800	8 375	4 370	9 635	4 375	9 645
400	58	3 410	7 520	3 750	8 265	4 010	8 840	4 610	10 165	4 625	10 195
450	65	3 870	8 530	4 250	9 370	4 550	10 030	5 230	11 530	5 000	11 685
500	73	4 100	9 040	4 500	9 920	4 820	10 625	5 540	12 215	5 600	12 345
550	80	4 550	10 030	5 000	11 025	5 350	11 795	6 150	13 560	6 150	13 560

Maximum inflation pressure 550 kPa.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
325	85	245	65	200	55	102	225	302	665

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618A	T545447	TR 218 A