



Nokian Forest Rider 600/65R34 – T445460

SB = STEEL BELTED

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern Forest	Steel belted	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Max inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	mm	32 nds in	mm	32 nds in		
Ø T445460	600/65R34	165 A8 / 172 A2	Rider	SB	TL	DW20B	W18L	600	23.6	1 644	64.7	763	30.0	5 008	197.2	400	58	50	63	43	54

⊗ Production ended

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	2 960	6 525	3 250	7 165	3 480	7 670	4 000	8 820	4 000	8 820
200	29	3 320	7 320	3 650	8 045	3 910	8 620	4 490	9 900	4 500	9 920
240	35	3 750	8 265	4 125	9 095	4 410	9 720	5 070	11 175	5 000	11 025
280	41	4 100	9 040	4 500	9 920	4 820	10 625	5 540	12 215	5 600	12 345
320	46	4 440	9 790	4 875	10 745	5 220	11 510	6 000	13 230	6 000	13 230
360	52	4 690	10 935	5 150	11 355	5 510	12 145	6 330	13 955	6 300	13 890

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
573	150	430	115	350	90	180	395	530	1 170

Maximum inflation pressure 400 kPa without increase to the above load capacity values.

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618A	T55394	TR 218 A