



Nokian Forest Rider 710/55R34 – T445455

SB = STEEL BELTED

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern Forest	Steel belted	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Max inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	mm	32 nds in	mm	32 nds in
☞ T445455	710/55R34	171 A8 / 178 A2	Rider	SB	TL	DW24B	DW23B	710	28.0	1 640	64.6	755	29.7	4 977	195.9	400	58	50	63	43	54

☞ Production ended

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	3 320	7 320	3 650	8 045	3 910	8 620	4 490	9 900	4 500	9 920
200	29	3 750	8 265	4 125	9 095	4 410	9 720	5 070	11 175	5 000	11 025
240	35	4 210	9 280	4 625	10 195	4 950	10 915	5 690	12 545	5 600	12 345
280	41	4 550	10 030	5 000	11 025	5 350	11 795	6 150	13 560	6 150	13 560
320	46	4 950	10 915	5 450	12 015	5 830	12 855	6 700	14 770	6 700	14 770
360	52	5 280	11 640	5 800	12 785	6 210	13 690	7 130	15 720	7 100	15 655
400	58	5 600	12 345	6 150	13 560	6 580	14 505	7 560	16 665	7 500	16 535

Maximum inflation pressure 400 kPa.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
677	180	510	135	420	110	210	465	630	1 390

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618A	T55394	TR 218 A