



Nokian Forest Rider 710/70R34 – T445517

SB = STEEL BELTED

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern Forest	Steel belted	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Max inflation pressure		Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	mm	32 nds in	mm	32 nds in
Ø T445517	710/70R34	176 A8 / 183 A2	Rider	SB	TL	DW24B	DW23B	710	28.0	1 844	72.6	841	33.1	5 592	220.2	400	58	53	67	46	58

⊗ Production ended

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	4 100	9 040	4 500	9 920	4 820	10 625	5 540	12 215	5 600	12 345
200	29	4 690	10 340	5 150	11 355	5 510	12 145	6 330	13 955	6 300	13 890
240	35	5 280	11 640	5 800	12 785	6 210	13 690	7 130	15 720	7 100	15 655
280	41	5 730	12 630	6 300	13 890	6 740	14 860	7 750	17 085	7 750	17 085
320	46	6 100	13 450	6 700	14 770	7 170	15 805	8 240	18 165	8 250	18 190
360	52	6 460	14 240	7 100	15 655	7 600	16 755	8 730	19 245	8 750	19 290

Maximum inflation pressure 400 kPa without increase to the above load capacity values.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
950	250	715	190	585	155	298	655	883	1 945

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55388	TR 218 A