



## Nokian HTS G2 E-4 18.00-25 PR40 – T445637

TL = TUBELESS, may be fitted with or without tube

Product code	Size	PR	Pattern	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Max. inflation pressure		Load capacity kg/lbs								Total tread depth					
							mm	in	mm	in	mm	in	mm	in	kPa	psi	Forklift trucks				Other vehicles				mm	32 nds in				
																	25 km/h / 15 mph		35 km/h / 22 mph		10 km/h		5 mph				25 km/h		15 mph	
Steering	Drive	Steering	Drive	10 km/h	5 mph	25 km/h	15 mph	mm	32 nds in																					
T445637	18.00-25	40	HTS G2 E-4	TL	13.00/2.5	15.00/2.5	500	19.7	1667	65.6	770	30.3	5000	196.9	1000	145	17 500	38 580	22 750	50 155	16 190	35 690	21 875	48 225	22 750	50 155	17 500	38 580	57	72

### LOAD & SPEED TABLE AT 1000 KPA

Counter balanced lift trucks				Other vehicles	
Load wheel		Steering wheel		Speed km/h	Load kg
Speed km/h	Load kg	Speed km/h	Load kg		
0	26 420	0	26 420	0	26 420
1	26 270	1	26 060	1	26 050
2	26 120	2	25 700	2	25 690
3	25 980	3	25 340	3	25 320
4	25 830	4	24 990	4	24 950
5	25 690	5	24 630	5	24 580
6	25 540	6	24 270	6	24 220
7	25 390	7	23 920	7	23 850
8	25 250	8	23 560	8	23 480
9	25 100	9	23 200	9	23 110
10	24 960	10	22 850	10	22 750
11	24 810	11	22 490	11	22 400
12	24 660	12	22 130	12	22 050
13	24 520	13	21 780	13	21 700
14	24 370	14	21 420	14	21 350
15	24 230	15	21 060	15	21 000
16	24 080	16	20 710	16	20 650
17	23 930	17	20 350	17	20 300
18	23 790	18	19 990	18	19 950
19	23 640	19	19 640	19	19 600
20	23 500	20	19 280	20	19 250
21	23 350	21	18 920	21	18 900
22	23 200	22	18 570	22	18 550
23	23 060	23	18 210	23	18 200
24	22 910	24	17 850	24	17 850
25	22 750	25	17 500	25	17 500