



# Nokian Nordman Forest TRS L-2 600/65-34 20PR – T445475

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Nordman Forest	Steel fortified	TT/TL	Recommended rim	Width		Diameter		Loaded static radius		Rolling circumference		Max. Inflation pressure		Tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	mm	32 nds in	mm	32 nds in		
T445475	600/65-34	163 A8 / 170 A2	20	TRS L-2	SF	TT	DW20B	600	23.6	1 644	64.7	755	29.7	4 964	195.4	360	52	51	64	41	52

## LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	3 250	7 165	3 480	7 670	4 000	8 820	4 000	8 820
200	29	3 650	8 045	3 910	8 620	4 500	9 920	4 500	9 920
240	35	4 125	9 095	4 410	9 720	5 000	11 025	5 000	11 025
280	41	4 500	9 920	4 820	10 625	5 600	12 345	5 600	12 345
320	46	4 875	10 745	5 220	11 510	6 000	13 230	6 000	13 230

## LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
595	155	445	120	366	95	187	410	553	1 220

Maximum pressure / Track pressure 360 kPa/52 psi

## TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55394	TR 218 A