



## Nokian Nordman Forest TRS L-2 700/55-34 20PR – T445476

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Nordman Forest	Steel fortified	TT/TL	Recommended rim	Width		Diameter		Loaded static radius		Rolling circumference		Max. Inflation pressure		Tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	mm	32 nds in	mm	32 nds in
T445476	700/55-34	166 A8 / 173 A2	20	TRS L-2	SF	TT	DW24B	700	27.6	1 630	64.2	751	29.6	4 938	194.4	360	52	51	64	41	52

### LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	3 550	7 825	3 800	8 375	4 375	9 645	4 375	9 645
200	29	4 000	8 820	4 280	9 435	4 875	10 745	4 875	10 745
240	35	4 500	9 920	4 820	10 625	5 600	12 345	5 600	12 345
280	41	5 000	11 025	5 350	11 795	6 150	13 560	6 150	13 560
320	46	5 300	11 685	5 670	12 500	6 500	14 330	6 500	14 330

### LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
700	185	525	140	431	115	220	485	650	1 435

Maximum pressure / Track pressure 360 kPa/52 psi

### TUBES AND VALVES

**USE ALWAYS WITH TUBE**

Tube product code	Valve tube-type
T55394	TR 218 A