



Nokian Nordman Forest TRS L-2 700/70-34 20PR – T445596

SF = STEEL FORTIFIED TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern Nordman Forest	Steel fortified	TT/TL	Recommended rim	Width		Diameter		Loaded static radius		Rolling circumference		Max. Inflation pressure		Tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	mm	32 nds in	mm	32 nds in
T445596	700/70-34	173 A8 / 180 A2	20	TRS L-2	SF	TT	DW20B	700	27.6	1 844	72.6	840	33.1	5 542	218.2	360	52	53	67	43	54

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs
160	23	4 375	9 645	4 680	10 320	5 380	11 860	5 380	11 860
200	29	5 000	11 025	5 350	11 795	6 150	13 560	6 150	13 560
240	35	5 600	12 345	5 990	13 205	6 890	15 190	6 900	15 210
280	41	6 150	13 560	6 580	14 505	7 560	16 665	7 500	16 535
320	46	6 500	14 330	6 960	15 345	8 000	17 635	8 000	17 635

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
950	250	715	190	585	155	298	655	883	1 945

Maximum pressure / Track pressure 360 kPa/52 psi

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55388	TR 218 A